



Delft University of Technology

Monitoring changes inside subsurface layers using non-physical reflections retrieved from seismic interferometry

Shirmohammadi, F.; Draganov, D.S.; Wapenaar, C.P.A.

Publication date

2020

Document Version

Accepted author manuscript

Citation (APA)

Shirmohammadi, F., Draganov, D. S., & Wapenaar, C. P. A. (2020). *Monitoring changes inside subsurface layers using non-physical reflections retrieved from seismic interferometry*. Poster session presented at NAC 2020, Utrecht, Netherlands.

Important note

To cite this publication, please use the final published version (if applicable). Please check the document version above.

Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.
We will remove access to the work immediately and investigate your claim.

Monitoring changes inside subsurface layers using non-physical reflections retrieved from seismic interferometry

Faezeh Shirmohammadi⁽¹⁾, Deyan Draganov⁽¹⁾ and Kees Wapenaar⁽¹⁾

*(1) Department of Geoscience and Engineering, Delft University of Technology, Delft, Netherlands
Email: F.shirmohammadi@tudelft.nl*

Seismic interferometry (SI) is a principle for retrieving responses between two receivers using cross-correlation. After the retrieval, one of the receivers acts as a virtual seismic source whose response is retrieved at the second receiver. Correct response retrieval relies on assumptions, among other, of a lossless medium being illuminated homogeneously by sufficiently densely spaced sources (passive or active). When these assumptions are not met, non-physical reflections might appear in the results of SI due to insufficient destructive interference. These non-physical reflections are caused by internal reflections inside subsurface layers. However, the non-physical reflections could be used for monitoring changes in the subsurface layers that generate them.

We investigate utilization of non-physical reflections for monitoring velocity changes for purposes of the DeepNL programme. We simulate reflection experiments using an acoustic finite-difference modelling for a horizontally layered model and for a subsurface with inclined layers. We perform SI by autocorrelation and by cross-correlation. Comparing retrieved results with the directly modelled results, we confirm previous results that for a layered subsurface the retrieved ghost reflections can be used for multiple offsets. For inclined layers, zero-offset ghost reflections can be retrieved for the different receiver locations. Both types of non-physical reflections are sensitive to velocity change and thickness of the layer that cause them to appear in the SI results, so they can be used for monitoring purposes of the subsurface.

Keywords: Seismic interferometry, non-physical reflection, monitoring, subsurface, seismics, DeepNL