

## Integrated monitoring and evaluation of pilot with longitudinal training walls

Buijse, Tom ; Mosselman, Erik; Eerden, Henk; Collas, Frank ; Verbrugge, Laura; Paarlberg, Andries; Omar, Amgad; de Jong, Jurjen; Chavarrías, Víctor; More Authors

### Publication date

2023

### Document Version

Final published version

### Citation (APA)

Buijse, T., Mosselman, E., Eerden, H., Collas, F., Verbrugge, L., Paarlberg, A., Omar, A., de Jong, J., Chavarrías, V., & More Authors (2023). *Integrated monitoring and evaluation of pilot with longitudinal training walls*. 11-11. Abstract from 5th International Conference on the Status and Future of the World's large rivers 2023, Vienna, Austria.

### Important note

To cite this publication, please use the final published version (if applicable).  
Please check the document version above.

### Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

### Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.  
We will remove access to the work immediately and investigate your claim.

## Integrated Monitoring and Evaluation of Pilot with Longitudinal Training Walls

Mr. Tom Buijse<sup>1,3</sup>, Mr. Erik Mosselman<sup>1,2</sup>, Mr. Henk Eerden<sup>5</sup>, Mr. Frank Collas<sup>4,5</sup>, Ms. Laura Verbrugge<sup>4,6</sup>, Mr. Andries Paarlberg<sup>7</sup>, Mr. Amgad Omer<sup>1</sup>, Mr. Jurjen de Jong<sup>1,8</sup>, Mr. Víctor Chavarrías<sup>1</sup>, Mr. Willem Ottevanger<sup>1</sup>, Ms. Rolien van der Mark<sup>1</sup>, Mr. Remi van der Wijk<sup>1</sup>, Ms. Nathalie Asselman<sup>1</sup>

<sup>1</sup>Deltares, DELFT, Netherlands.

<sup>2</sup>Delft University of Technology, DELFT, Netherlands.

<sup>3</sup>Wageningen University, Wageningen, Netherlands.

<sup>4</sup>Radboud University, Nijmegen, Netherlands.

<sup>5</sup>Rijkswaterstaat, Arnhem, Netherlands.

<sup>6</sup>Aalto University, Aalto, Finland.

<sup>7</sup>HKV Consultants, Lelystad, Netherlands.

<sup>8</sup>Sweco, Stockholm, Sweden.

The river Waal is the main branch of the river Rhine in the delta in the Netherlands. It has been trained with groynes in the 19th century to reduce flooding risk due to ice jams and to improve navigability. The resulting narrower main channel, however, has triggered bed erosion and lowered low-flow water levels at a rate of meters per century with increasing adverse effects. For instance, hydraulic structures become unstable, pipeline and cable crossings are exposed, obstacles appear for navigation, and inundation depths and frequencies of floodplain and wetland habitats are reduced. To mitigate the adverse effects while maintaining the benefits of river training, Rijkswaterstaat launched the idea of a new system of river training. It replaces the existing system of a single main channel between groynes by two parallel channels, separated by a longitudinal training wall. To test this new system, Rijkswaterstaat implemented a 10-km long pilot with three longitudinal training walls in the river Waal in the years 2014-16. Before, during and after implementation, an extensive monitoring and research program was executed by the Waal Samen partnership consisting of Rijkswaterstaat, Koninklijke BLN-Schuttevaer, Sportvisserij Nederland, Hengelsportfederatie Midden-Nederland, Deltares, and the universities of Nijmegen, Wageningen, Delft and Twente. The new system was found to improve navigability at low flows if applied in reaches of least available depth. Moreover, it was found to sustain long-term navigability by countering the ongoing overall incision of the river bed. After implementation of the pilot, the waterway continued satisfying the international navigability standards. The pilot substantially improved the quality of nature in the reach of the training walls. The walls lowered design flood water levels at least as much as the groyne lowering previously planned in this reach. A modestly positive effect was found on freshwater supply during droughts. Participation of stakeholders in the monitoring and research program was found to have increased support and appreciation for the pilot. We conclude that the system tested in the pilot opens perspectives for integral solution of several river problems. It performs better than the old system with groynes thanks to spatial diversification through separation of functions. No unforeseen negative impacts have surfaced. A longer pilot reach monitored over a longer period would be required for solid conclusions about the extent to which the new system solves all river problems, but at any rate it offers more space for further improvements in the future than the old system. Rijkswaterstaat and Deltares jointly identified three points of further attention: (i) regulation of flow and sediment transport by modifying inlet sills; (ii) operation and maintenance; (iii) the inland waterway. We recommend addressing these points by continued monitoring and close consultation of the inland waterway transport sector.