

## Modelling episodic induced seismicity with poroelastic dynamic rupture and large-scale wavefield propagation

Ruan, J.; Ghose, R.; Mulder, W.A.

### Publication date

2020

### Document Version

Accepted author manuscript

### Citation (APA)

Ruan, J., Ghose, R., & Mulder, W. A. (2020). *Modelling episodic induced seismicity with poroelastic dynamic rupture and large-scale wavefield propagation*. Abstract from GeoUtrecht 2020, Netherlands.

### Important note

To cite this publication, please use the final published version (if applicable).  
Please check the document version above.

### Copyright

Other than for strictly personal use, it is not permitted to download, forward or distribute the text or part of it, without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license such as Creative Commons.

### Takedown policy

Please contact us and provide details if you believe this document breaches copyrights.  
We will remove access to the work immediately and investigate your claim.

## **Modelling episodic induced seismicity with poroelastic dynamic rupture and large-scale wavefield propagation**

**Jingming Ruan<sup>1</sup>, Ranajit Ghose<sup>1</sup>, Wim Mulder<sup>1,2</sup>**

<sup>1</sup> Delft University of Technology, the Netherlands

<sup>2</sup> Shell Global Solutions International BV, the Netherlands

Modelling dynamic rupture is essential to correctly describe the process of induced seismicity. Defmod, an open-source finite-element code featuring quasi-static loading, co-seismic volumetric strain, and dynamic rupture, is used to simulate the entire chain of induced seismicity, from pressure evolution due to fluid injection and extraction, building up of stress, and nucleation of dynamic faulting, to wavefield propagation towards the surface. To study induced earthquakes caused by fluid extraction, we modelled the behaviour of a 2-D poroelastic medium including a predefined fault by assigning a fluid source, either constant or varying, in a homogeneous reservoir layer to induce a pressure-field change. For each quasi-static step, the pressure field difference generates a displacement field that in turn affects the pressure through a coupling matrix, depending on Biot's coefficient. The rate of pressure variation is subject to the fluid source as well as the material properties, e.g., porosity and fluid mobility, which affect the speed and distribution of the stress build-up on the fault and thus the pattern of rupture nucleation. In addition, we implemented a predefined pressure profile to simulate the induced rupture in case of a uniform depletion of the reservoir to allow for a comparison with other studies. The results provide useful insights on the causality between reservoir-pressure behaviour and the induced seismicity.